



DESCRIPTION

The is a competitive high performance 16 inputs to 2 outputs routing switcher. Designed for HDMI™ signal, Support Digital Video TMDS format and Digital Audio via HDMI™ 19 Pin connectors. This product is certified as being fully HDMI™ and HDCP 2.0 compliant. Providing 16 HDMI™ device inputs and 2 HDMI™ device outputs. The Switcher support HDMI™ 1.4a 3D formats the data rate up to 2.25Gbps. Also control any one of the 16 inputs to 2 outputs via press the selection buttons on the front panel. Control by selection buttons on the front panel, IR Remote controller and RS-232 via a PC. The product approved the CE & FCC compliants. Support high resolution 1080p quality HDMI™ sources to a HDMI™ display, monitor or projector.

SPECIFICATION

Type of Switcher	: 16×2 HDMI Routing Switcher
Type of Signal	: TMDS Digital Video PCM Digital Audio
Compliant with HDMI standard	: HDMI and HDCP 2.0
HDTV Support	: 1080p HDMI formats and UXGA 1600×1200
Data Rates	: 225Mbps
HDMI Cable Distance	: 15 meters (49 feet)
Infrared frequency	: 38KHz
Controls	: RS-232, IR, IR EXT, Select buttons (on the front panel)
Dimension (WxDxH)	: 17.32 x 7.87 x 1.74 (440mm x 200mm x 44mm)
Weight	: 2.45 Kg / 5.4 lb
Power Supply	: DC12V / 3A Max Use Universal Switch Type 50/60Hz, 100~240VAC



INPUT : 16X HDMI
OUTPUT : 2X HDMI

SUPPORT HDMI 1.4A 3D FORMATS MAX DATA RATE 2.25GBPS
HDTV COMPATIBLE AND HDCP 2.0 COMPLIANT
CONTROL BY PRESS BUTTONS ON THE FRONT PANEL
SUPPORT THE RS-232 SERIAL PORT INTERFACE



Webpage



Youtube

